

# Scotch® Performance Masking Tape 231/231A\*



Technical Data

February, 2005

\*231A designation was added 12/04 for aerospace market.

**Product Description** Scotch® Performance Masking Tape 231/231A is a premium high performance crepe paper masking tape designed to perform well in most industrial painting situations, including the use of bake cycles. This smooth to the touch masking tape, embodies all the features that are desirable of a paint masking tape and designed specifically for the professional painter.

Construction	Backing	Adhesive	Color	Standard Roll Length
	Smooth mini-crepe paper, treated with a heat resistant saturant.	Rubber	Tan	55 m (60.15 yds.)

**Typical Physical Properties** **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	38 oz./in. width (41 N/100 mm width)	D-3330
Tensile Strength:	28 lbs./in. width (490 N/100 mm width)	D-3759
Elongation at Break:	10%	D-3759
Tape Thickness:	7.6 mils (0.19 mm)	D-3652
Temperature Use Range:	Up to 300°F (149°C) for up to 30 min. Removes cleanly	

- Features**
- Can be qualified to meet Federal Specification PPP-T-42C, Type I, (CID-A-A-883B).
  - Rubber adhesive with instant adhesion that sticks easily and allows fast application.
  - Good holding power that resists lifting or curling that helps reduce rework.
  - Superior adhesive transfer resistance with clean removal that helps reduce rework.
  - Smooth mini-crepe backing results in excellent surface contact with very secure holding.
  - Excellent conformability and easy handling that reduces time involved in application.
  - The backing is solvent and moisture resistant that helps reduce bleed-through minimizing rework.
  - The backing has excellent dead stretch for minimal recovery that reduces rework.
  - Easy to tear backing aids in handling, yet strong enough to resist slivering giving one piece removal to help reduce labor.
  - Special backsize treatment gives a balanced unwind that helps reduce waste.
  - Paint flake resistance that reduces rework due to contamination, results in a quality paint job.
  - Designed for indoor use only as it should not be subjected to outdoor exposure for prolonged periods of sunlight as the tape may become very difficult to remove. Best results are obtained if applied and removed within 24 hours.

# Scotch® Paint Masking Tape

231/231A

---

**Application Ideas**      • Scotch® Performance Masking Tape 231/231A is well suited for painting on automobiles, aircraft, trucks, boats and painting of fabricated parts.

---

**Storage**      Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

---

**Shelf Life**      To obtain best performance, use within one year from date of manufacture.

---

**Product Use**      All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

---

**Warranty and Limited Remedy**      Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

---

**Limitation of Liability**      Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



**Industrial Business  
Industrial Adhesives and Tapes Division**

3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (fax)  
www.3M.com/industrial



*Recycled Paper  
40% pre-consumer  
10% post-consumer*

Printed in U.S.A.  
©3M 2005 70-0709-4425-4 (2/05)